

SUPERAIR



รับประกันคอมเพรสเซอร์ 10 ปี
รับประกันตัวเครื่อง 5 ปี
ฟรีค่าบริการหลังการขายการบริการ 5 ปีแรก*
*ฟรีการบริการ 5 ปีแรก ตามเงื่อนไขบริษัท

Ceiling Type Inverter/R32



*Human Sensor (Optional): HCFI-36ETR32

Model		Set	HCFI-18PSR32	HCFI-25PSR32	HCFI-30PSR32	HCFI-36PSR32
		Indoor	HCFI-18PSR32F	HCFI-25PSR32F	HCFI-30PSR32F	HCFI-36PSR32F
Outdoor			1U-18SIR32CP	1U-25SIR32CP	1U-30SIR32CP	1U-36SIR32CP
Power supply		V/Ph/Hz	220/1/50	220/1/50	220/1/50	220/1/50
Rated cooling	Capacity	KW	5.3 (2.2-5.8)	7.3 (2.6-8.0)	8.8 (3.6-10.0)	10.5 (4.0-11.2)
	Capacity	Btu/h	19,461(7,500-19,800)	25,000(9,000-27,300)	30,070(12,200-34,100)	36,915(13,600-38,200)
	Input	W	1480	2320	2610	3330
	Running current	A	6.80	10.65	11.98	15.29
	SEER	/	19.62	17.23	17.88	16.38
Egat		/	5★	5	5★	5
Max. input consumption		W	2000	3000	3400	4100
Max. current		A	9.18	12.40	15.61	18.82
Min. input consumption		W	490	500	770	228
Operation Control (Standard)		Remote	YL-HQ501	YL-HQ501	YL-HQ501	YL-HQ501
Operation Control (Optional)		Wired	YR-E17A	YR-E17A	YR-E17A	YR-E17A
WiFi Control / Human Sensor		Wi-Fi / Human	Wi-Fi / Wi-Fi	Wi-Fi / Wi-Fi	Wi-Fi / Wi-Fi	Wi-Fi / Wi-Fi
Indoor air flow (SH/H/M/L)		m³/h	1000/760/600/500	1050/800/700/550	1400/1300/1180/1060	1600/1400/1280/1160
Indoor noise level (SH/H/M/L)		dB(A)	43/40/38/35	45/42/39/36	45/43/40/37	47/43/41/37
Indoor dimension	Unit (LxWxH)	(mm)	1000*230*680	1000*230*680	1325*230*680	1650 x 230 x 680
	Packing (LxWxH)	(mm)	1100*305*779	1100*305*779	1425*305*779	1425*305*779
Drainage pipe (material/LD/O.D)		Ø(mm)	16/20	16/20	16/20	16/20
Indoor weight		Net/Gross weight (Kg)	26/32	27/33	33.5/41.9	33.5/41.9
Compressor	Brand		Mitsubishi Electric	Mitsubishi Electric	Mitsubishi Electric	Mitsubishi Electric
	Type		Rotary	Rotary	Rotary	Rotary
Outdoor air flow		m³/h	2500	2500	3500	3800
Outdoor noise level		dB(A)	54	54	57	59
Outdoor dimension	Unit (LxWxH)	mm	820 x 338 x 614	820 x 338 x 614	920 x 372 x 760	920 x 372 x 760
	Packing(LxWxH)	mm	977 x 400 x 735	977 x 400 x 735	1085 x 487 x 843	1085 x 487 x 843
Outdoor weight		Net/Gross weight kg	38/42	38/42	52/57	57/62
Refrigerant	Type		R32	R32	R32	R32
	Charge	g	970	1130	1280	1500
	Additional weight	g/m	20	45	45	45
Refrigerant pipe	Liquid /Gas side	mm	6.35 /12.70	9.52 /15.88	9.52/15.88	9.52/15.88
	Max. length	m	20	20	25	30
	Max. height	m	10	10	10	20
	Min. length	m	5.00	5.00	5.00	5.00
Operation temperature range		°C	16~30	16~30	16~30	16~30



HCFI-36ETR32	HCFI-40ESR32	HCFI-40ETR32	HCFI-48ESR32	HCFI-48ETR32	HCFI-60ETR32
HCFI-36ETR32F	HCFI-40ESR32F	HCFI-40ETR32F	HCFI-48ESR32F	HCFI-48ETR32F	HCFI-60ETR32F
1U-36T3R32C	1U-40SIR32C	1U-40T3R32C	1U-48SIR32C	1U-48T3R32C	1U-60T3R32C
380/3/50	220/1/50	380/3/50	220/1/50	380/3/50	380/3/50
10.2(5.0-11.2)	11.6(5.7-13.0)	11.6(5.7-13.0)	14.1(6.2-14.7)	14.1(6.2-14.7)	16.0(4.5-16.5)
38,000(17,100-38,200)	40,900(19,500-44,000)	40,900(19,500-44,000)	50,880(21,200-51,000)	51,225(21,200-52,000)	57,832(15,400-58,000)
3300	4100	4100	5714	5263	5390
5.48	16.65	6.58	26.20	8.70	9.10
17.15	17.15	18.27	14.77	15.25	17.03
5	5	5★	5	5	5★★
4000	5100	5100	7000	7000	6500
6.54	23.6	8.42	32.4	11.68	10
830	950	950	1000	1000	1000
YL-HQ501	YL-HQ501	YL-HQ501	YL-HQ501	YL-HQ501	YL-HQ501
Ø / Ø	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A
Ø / Ø	Ø / Ø	Ø / Ø	Ø / Ø	Ø / Ø	Wi-Fi / Wi-Fi
1600/1400/1280/1160	2050/1900/1600/1400	2050/1900/1600/1400	2150/1980/1800/1600	2150/1980/1800/1600	2250/2000/1850/1650
47/43/41/37	48/44/42/38	48/44/42/38	50/46/43/40	50/46/43/40	52/48/45/42
1325 x 230 x 680	1650 x 230 x 680	1650 x 230 x 680	1650 x 230 x 680	1650 x 230 x 680	1650 x 230 x 680
1425 x 305 x 779	1750 x 305 x 779	1750 x 305 x 779	1750 x 305 x 779	1750 x 305 x 779	1750 x 305 x 779
16/20	16/20	16/20	16/20	16/20	16/20
33.5/41.9	41.8/49.5	41.8/49.5	41.8/49.5	41.8/49.5	44/51.5
Mitsubishi Electric	Mitsubishi Electric	Mitsubishi Electric	Mitsubishi Electric	Mitsubishi Electric	Mitsubishi Electric
Rotary	Rotary	Rotary	Rotary	Rotary	Rotary
3800	5000	5000	5500	5500	7400
56.00	58.00	58.00	59.00	59.00	59.00
920 x 372 x 760	950 x 370 x 965	950 x 370 x 965	950 x 370 x 965	950 x 370 x 965	950 x 370 x 1350
1085 x 487 x 843	1050 x 450 x 1095	1050 x 450 x 1095	1050 x 450 x 1095	1050 x 450 x 1095	1050 x 485 x 1500
60/65	76/86	76/86	76/86	76/86	101/116
R32	R32	R32	R32	R32	R32
1650	1900	1900	1900	1900	3500
45	45	45	45	45	45
9.52 /15.88	9.52 /15.88	9.52 /15.88	9.52 /15.88	9.52 /15.88	9.52 /19.05
30.00	50.00	50.00	50.00	50.00	70.00
20.00	30.00	30.00	30.00	30.00	30.00
5.00	5.00	5.00	5.00	5.00	5.00
16~30	16~30	16~30	16~30	16~30	16~30

*Wi-Fi PM 2.5 Filter; Human Sensor; Smart Control (Optional): HCFI-36ETR32, HCFI-40ESR32, HCFI-40ETR32, HCFI-48ESR32, HCFI-48ETR32

Ceiling Type

Ceiling Type