

SUPERAIR

Round Flow

Cassette Type Fixed Speed / R32



รับประกันคอมเพรสเซอร์ 5 ปี
รับประกันตัวเครื่อง 5 ปี
ฟรีค่าบริการหลังการขายทุกรายการ 5 ปีแรก*
*ฟรีทุกรายการ 5 ปีแรก ตามเงื่อนไขบริษัท



Model		Set	HCSU-18BSR32	HCSU-25BSR32	HCSU-30BSR32
		Indoor	HCSU-18BSR32F	HCSU-25BSR32F	HCSU-30BSR32F
		Outdoor	1C-18S1R32C	1C-25S1R32C	1C-30S1R32C
Power supply	Capacity	Ph/v/Hz	1/220/50	1/220/50	1/220/50
	Power Consumption	Btu/h	18,000	25,000	30,000
	Running current	W	1450	1820	2530
	SEER	A	6.66	8.36	11.62
	Energy Class	BTU/hr/W	13.41	13.48	12.97
Maximum fuse amps (MFA)			5	5	5
Remote Controller (S)			YL-HRS01	YL-HRS01	YL-HRS01
Wired Controller (O)			YR-E17A	YR-E17A	YR-E17A
Indoor	Indoor air flow (SH/H/M/L)	m ³ /h	1050/930/660/600	1300/1000/800/600	1600/1400/1280/1160
	Indoor noise level (SH/H/M/L)	dB(A)	45/42/39/35	47/44/41/37	49/46/43/39
	Panel Model		PB-950QB	PB-950QB	PB-950QB
	External dimensions(WxDxH)	mm	950 x 950 x 50	950 x 950 x 50	950 x 950 x 50
	Shipping dimensions(WxD xH)	mm	1013 x 1035 x 125	1013 x 1035 x 125	1013 x 1035 x 125
Panel	Panel Net/Shipping Weight	kg	5.5 / 8.5	5.5 / 8.5	5.5 / 8.5
	Unit (LxWxH)	mm	840 x 840 x 202	840 x 840 x 244	840 x 840 x 244
	Packing (LxWxH)	mm	978 x 978 x 269	978 x 978 x 312	978 x 978 x 312
	Net/Gross weight	kg	22 / 27	25 / 30	25 / 30
	Outdoor air flow	CFM	2000	2000	3500
Outdoor	Outdoor air flow	m ³ /h	1177	1177	2060
	Outdoor noise level	dB(A)	53	54	55
	Tube Material		Inner Grooved copper	Inner Grooved copper	Inner Grooved copper
	Compressor	Type	Rotary	Rotary	Rotary
	Compressor	Brand	HIGHLY	HIGHLY	HIGHLY
Outdoor Dimension	Unit (LxWxH)	mm	890 x 340 x 705	890 x 340 x 705	920 x 372 x 760
	Packing(LxWxH)	mm	1046 x 460 x 780	1046 x 460 x 780	1085 x 487 x 843
	Net/Gross weight	kg	46 / 49.5	49.5 / 53	54 / 59
	Type		R32	R32	R32
	Additional weight	g/m	120g+(B-10)×45g	120g+(B-10)×45g	120g+(B-10)×45g
Refrigerant	Liquid side	mm	9.52	9.52	9.52
	Gas side	mm	15.88	15.88	15.88
	Max. length	m	20	20	20
	Max. height	m	10	10	10
	Min. length	m	5	5	5
Operation temperature range		°C	16-30	16-30	16-30
Ambient temperature range		°C	18-43	18-43	18-43



HCSU-36BSR32	HCSU-36BTR32	HCSU-40BSR32	HCSU-40BTR32	HCSU-48BTR32
HCSU-36BSR32F	HCSU-36BTR32F	HCSU-40BSR32F	HCSU-40BTR32F	HCSU-48BTR32F
1C-36S1R32C	1C-36T3R32C	1C-40S1R32C	1C-40T3R32C	1C-48T3R32C
1/220/50	3/380/50	1/220/50	3/380/50	3/380/50
36,000	36,000	40,000	40,000	48,000
3020	3370	3370	4630	4630
13.87	5.10	15.47	5.69	7.82
12.62	13.03	13.31	13.00	12.11
5	5	5★	5	5★★
27.00	9.75	32.25	11.70	13.20
YL-HRS01	YL-HRS01	YL-HRS01	YL-HRS01	YL-HRS01
YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A
1800/1600/1500/1250	1800/1600/1500/1250	1950/1800/1600/1300	1950/1800/1600/1300	2100/1980/1800/1600
50/47/44/40	50/47/44/40	52/49/46/42	52/49/46/42	53/50/47/42
PB-950QB	PB-950QB	PB-950QB	PB-950QB	PB-950QB
950 x 950 x 50	950 x 950 x 50	950 x 950 x 50	950 x 950 x 50	950 x 950 x 50
1013 x 1035 x 125	1013 x 1035 x 125	1013 x 1035 x 125	1013 x 1035 x 125	1013 x 1035 x 125
5.5 / 8.5	5.5 / 8.5	5.5 / 8.5	5.5 / 8.5	5.5 / 8.5
840 x 840 x 286	840 x 840 x 286	840 x 840 x 286	840 x 840 x 286	840 x 840 x 286
978 x 978 x 353	978 x 978 x 353	978 x 978 x 353	978 x 978 x 353	978 x 978 x 353
26 / 32	26 / 32	26 / 32	26 / 32	26 / 32
5000	5000	7000	7000	7000
2943	2943	4120	4120	4120
59	59	59	59	60
Inner Grooved copper	Inner Grooved copper	Inner Grooved copper	Inner Grooved copper	Inner Grooved copper
Rotary	Rotary	Rotary	Rotary	Rotary
HIGHLY	HIGHLY	HIGHLY	HIGHLY	HIGHLY
950 x 370 x 965	950 x 370 x 965	950 x 370 x 1350	950 x 370 x 1350	950 x 370 x 1350
1050 x 485 x 1095	1050 x 485 x 1095	1050 x 485 x 1095	1050 x 485 x 1500	1050 x 485 x 1500
74 / 85	74 / 85	89 / 103	91 / 105	91 / 105
R32	R32	R32	R32	R32
340g+(B-15)×45g	340g+(B-15)×45g	340g+(B-15)×45g	340g+(B-15)×45g	340g+(B-15)×45g
9.52	9.52	9.52	9.52	9.52
19.05	19.05	19.05	19.05	19.05
30	30	50	50	50
15	15	20	20	20
5	5	5	5	5
16-30	16-30	16-30	16-30	16-30
18-43	18-43	18-43	18-43	18-43

*น้ำยา R32 อยู่ในเครื่องมาตรฐานถนอมถนอม 10 เมตร ในรุ่น 18,000 - 30,000 Btu และ 15 เมตร ในรุ่น 36,000 - 48,000 แต่ค่าความยาวท่อเกินกว่าระยะที่กำหนดจะต้องเติมน้ำยาเพิ่มเติมตามข้อนี้